

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) An ink supply device, ~~which includes~~ comprising:
an ink tank for containing ink therein and a tank holder ~~for holding~~ configured to hold the ink tank in a detachable manner, wherein

the tank holder includes: ~~pressure control means for allowing the ink and air to circulate between the tank holder and the ink tank so that an internal pressure of the attached ink tank has a predetermined value~~

a pressure control chamber, the ink and air circulating via a circulation section between the pressure control chamber and the ink tank; and

an air supply section via which the ink tank communicates with an atmosphere external to the ink tank;

the air supply section absorbing a pressure change caused by a change in an amount of ink remaining in the ink tank, and

the pressure control chamber and the circulation section absorbing a pressure change caused by a temperature change in the ink tank.

2. (Canceled).

3. (Withdrawn). The ink supply device as set forth in Claim 1, wherein
the pressure control means includes air supply means for supplying the air into the inside of the ink tank from outside.

4. (Withdrawn) The ink supply device as set forth in Claim 1, wherein
a part of the pressure control means is inserted into the ink tank when the ink tank is attached to the tank holder.

5. (Currently Amended) The ink supply device as set forth in Claim 1, wherein:
the tank holder includes first ink supply ~~means~~ conduit in communication with the attached ink tank; and configured to supply ~~for supplying~~ the ink contained in the ink tank to outside the ink tank; and

the first ink supply ~~means-conduit~~ is configured ~~caused to be in communication~~ be the last part of the tank holder to engage with the ink tank ~~last~~, when the ink tank is ~~being~~ attached to the tank holder.

6. (Withdrawn) The ink supply device as set forth in Claim 1, wherein:
the tank holder includes first ink supply means in communication with the ink tank attached, for supplying the ink contained in the ink tank to outside; and
the first ink supply means has communication with the ink tank disengaged first when the ink tank is detached from the tank holder.

7. (Withdrawn) The ink supply device as set forth in Claim 1 wherein
the ink tank contains therein only the ink and the air.

8. (Currently Amended) The ink supply device as set forth in ~~Claim 2~~ Claim 1
wherein

the pressure control chamber includes at least a part of a side surface ~~made of~~ comprising
a biasing member, ~~which biases~~ configured to bias another surface so that the capacity of the
pressure control chamber becomes larger.

9. (Withdrawn) The ink supply device as set forth in Claim 1 wherein
the pressure control means is provided near a bottom surface of the ink tank.

10. (Withdrawn) The ink supply device as set forth in Claim 2 wherein
the pressure control chamber includes an ink absorber which has absorbed the ink
beforehand.

11. (Withdrawn) The ink supply device as set forth in claim 1 wherein
the pressure control means includes negative pressure control means for controlling the
internal pressure of the ink tank so as to be negative.

12. (Currently Amended) The ink supply device as set forth in ~~Claim 2~~ Claim 1
wherein

capacities V_s and V_t satisfy the following formula:

$$0.1 \leq V_s / V_t \leq 0.3$$

where V_t is the capacity of the ink tank and V_s is the capacity of the pressure control
chamber.

13. (Withdrawn) An ink supply device, which includes an ink tank for containing at least ink therein, comprising

capacity changing means for changing a capacity of the ink tank, according to a change in a state of a content inside the ink tank due to an environmental change outside the ink tank.

14. (Withdrawn) An ink supply device, which includes an ink tank for containing at least ink therein, comprising

pressure change control means for controlling a change in pressure, caused by consumption of the ink, inside the ink tank by supplying air to the inside of the ink tank from outside of the ink tank.

15. (Withdrawn) The ink supply device as set forth in Claim 13, comprising pressure change control means for controlling a change in pressure, caused by consumption of the ink, inside the ink tank by supplying air to the inside of the ink tank from outside of the ink tank.

16. (Withdrawn) The ink supply device as set forth in Claim 15, wherein:
the ink tank includes a first opening section and a second opening section; and
the capacity changing means and the pressure change control means are provided so as to respectively cover the first opening section and the second opening section.

17. (Withdrawn) The ink supply device as set forth in Claim 16 wherein:
the ink tank includes a third opening section for supplying the ink contained in the ink tank to the outside; and
only the third opening section and the pressure change control means is in communication with the outside of the ink tank.

18. (Withdrawn) The ink supply device as set forth in Claim 15, wherein
the capacity changing means is made of an elastic member.

19. (Withdrawn) The ink supply device as set forth in Claim 15, wherein
the capacity changing means changes the ink tank capacity by equal to or more than ten percent with respect to a pressure change per 1kPa inside the ink tank.

20. (Withdrawn) The ink supply device as set forth in Claim 15, wherein
the capacity changing means is arranged to generate a negative pressure inside the ink tank when the use of the ink supply device starts.

21. (Withdrawn) The ink supply device as set forth in Claim 15, wherein the pressure change control means controls the pressure change inside the ink tank by using the surface tension of the ink on a boundary face between the pressure change control means and the ink inside the ink tank.
22. (Withdrawn) The ink supply device as set forth in Claim 15, wherein the pressure change control means is made of a filter.
23. (Withdrawn) The ink supply device as set forth in Claim 22, wherein a mesh radius of the filter is between $25\mu\text{m}$ to $50\mu\text{m}$.
24. (Withdrawn) The ink supply device as set forth in Claim 17, comprising: second ink supply means being provided to a third opening section so as to cover the third opening section, the second ink supply means providing the ink to the outside in a case where the pressure outside the ink tank is equal to or less than a predetermined value.
25. (Withdrawn) The ink supply device as set forth in Claim 24 wherein:
the second ink supply means is made of a filter; and
the mesh radius of the filter is between $25\mu\text{m}$ to $50\mu\text{m}$.
26. (Withdrawn) The ink supply device as set forth in Claim 22, wherein surfaces of the filter are caused to be hydrophilic.
27. (Withdrawn) The ink supply device as set forth in Claim 15, wherein the capacity changing means is provided so that (i) a direction, in which the capacity changing means moves in order to change the capacity, and (ii) a direction, in which the ink supply device moves when the ink supply device is attached to a printing device and used, differ from each other.
28. (Withdrawn) The ink supply device as set forth in Claim 16, wherein the second opening section is provided at a bottom surface of the ink tank.
29. (Withdrawn) The ink supply device as set forth in Claim 24 wherein:
the third opening section is provided at a bottom surface of the ink tank; and
the second opening section and the third opening section are provided at a substantially same height.
30. (Withdrawn) The ink supply device as set forth in Claim 15, wherein the capacity changing means is provided inside the ink supply device.

31. (Withdrawn) The ink supply device as set forth in Claim 16, wherein the first opening section is provided at an upper surface of the ink tank.
32. (Withdrawn) The ink supply device as set forth in Claim 28, wherein the first opening section is provided at a bottom surface of the ink tank.
33. (Withdrawn) The ink supply device as set forth in Claim 13, wherein inside the ink tank, only the ink and the air is contained.
34. (New) The ink supply device of Claim 1, wherein said air supply section comprises an air supply passage whereby air freely communicates with the atmosphere external to the ink tank.
35. (New) The ink supply device of Claim 1, wherein said air supply section comprises an air supply passage whereby air freely communicates with an atmosphere external to both the ink tank and the tank holder.